

Specifications

Axxess

984-2 Two Chairs Ganged



Frame

- Arms/legs are 2" wide solid hardwood
- Frame components are double-doweled, glued and screwed
- Commercial grade engineered hardwood seat pan on steel supports
- Back frames connected with bolts and nuts
- Arms connected with counter-sunk machine screws
- 350 lb. capacity load rating per seat



Suspensions

- Seats and backs suspension built with Sytex 100% polyester sheet webbing applied with 1/2" staples at 45 degree angle, minimum of 3 staples per inch.
- Sytex suspension passes the following:
 - UFAC - Class 1
 - NFPA 260A - Class 1
 - CAL 117
 - FNE 83-258B

Dimensions

- Overall: 43.75"W x 24.75"D x 34.5"H
- Each Seat: 20"W x 19"D x 18.5"H
- Each Back: 20"W x 19"H
- Arm Height from Seat: 8.5"H (front)
- Arm Height From Floor: 27"H (front)

Foam

- CFC-free, Bio-Flex™ Hybrid includes soy-based foam
- Seat: 1.5" thick High Density Foam 1.8 Density 36 Compression
- Seat pad: 1" thick x 14 x 14 1.5 Density 33 CFR
- Back: 1.5" thick Foam 1.5 Density 33 Compression
- CAL 117 rated (CFR)

Warranty

- Limited Lifetime

Upholsteries

- Standard fabrics tested for high wear (most more than 30,000 double rubs Wyzenbeek Wire Mesh test).
- See individual upholstery specification sheet(s) for details regarding stain resistance, anti-microbial, moisture resistance, CAL-133 compliance, etc.
- Available in textile or coated fabric upholstery in a single or two-tone

Ships

Ships Fully Assembled by truck
Ship Weight: 84 lb.
Ship Cubes: 36

Exterior

- Exposed wood legs and arms of solid hardwood available in 12 standard finishes
- Sleek transitional style 1.25" square arms
- Rear leg gently curves to create a wall-saver design
- Separated seat/back simplifies cleaning
- Field replaceable seat and back ideal when soiled beyond normal cleaning/maintenance



Environmental & Sustainability
Materials & Resources



Standard material use in products in accordance with the following standards:

- LEED for Commercial Interiors EA Credit, 50% Construction Waste Diversion (1 point)
- LEED for Commercial Interiors EA Credit, 75% Construction Waste Diversion (1 point)
- ANSI/BIFMA e3-2017 (level®) Credit 6.4.2.2, 100% solid waste diversion
- LEED for Commercial Interiors EA Credit, Resource Reuse 30%, Furniture & Furnishings (1point) - HPFi Lifetime warranty and Second Life program applicable for reuse
- ANSI/BIFMA e3-2017 (level®) Credit 6.2.3, Extend Product Responsibility - HPFi Second Life program ensures reuse of usable product
- LEED for Commercial Interiors MR Credit, Regional Materials 20% (1 point) - HPFi products are manufactured in High Point, NC and may contribute this point based on project location.