Specifications

HPFi

Helix

580 & 580CB Dr. Stools

580

580CB

Features
- 11" diameter foot ring for hands-free height adjustment
- Dual-wheel compression braking casters inhibit movement when stool is vacant
- 5-Prong cast steel base
- 23" Base - Black powder coat (580) or chrome plated steel (580CB)
- Black powder coat (580) or chrome plated steel (580CB) cylinder travels 7.5"

Foam
- Foam
- CFC-free, Bio-Flex™ Hybrid includes soy-based foam
- Seat: 2.5" thick, Contour cut 2.5 Density 55 Ultra Cell

Upholstery
- Standard fabrics Cal 117 rated and tested for high wear (most more than 30,000 double rubs Wyzenbeek Wire Mesh test).
- Woven Cryptons treated with Perma Block or vinyls with Blockade/Nanocide which are anti-bacterial, anti-microbial and mildew resistant
- See individual swatches for technical specifications, Teflon/Scotchguard information, etc.
- Also accepts leather, faux leather and vinyl upholsteries

Dimensions
- Overall: 23"W x 23"D x 22.5-30"H
- Seat Height: 22.5" – 30"
- Seat Diameter: 16.5"
- Base Diameter: 23"
- Seat Thickness: 3"

Warranty
- Limited Lifetime
- 5 years on mechanical components
- Meets or exceeds applicable industry test standards

Ships
- Fully assembled
- Ship weight: 27 lb.
- Cu. ft.: 11
- Truck
- Freight Class: 250

Environmental & Sustainability
Materials & Resources

Standard material use in products in accordance with the following standards:

- LEED for Commercial Interiors EA Credit, 50% Construction Waste Diversion (1 point)
- LEED for Commercial Interiors EA Credit, 75% Construction Waste Diversion (1 point)
- LEED for Commercial Interiors EA Credit, Resource Reuse 30%, Furniture & Furnishings (1point) - HPFi Lifetime warranty and Second Life program applicable for reuse
- LEED for Commercial Interiors MR Credit, Regional Materials 20% (1 point) - HPFi products are manufactured in High Point, NC and may contribute this point based on project location.