



Specifications – Eve 5875IF 60° Curved Inside Facing Banquette



Frame

- Hardwood frames components are glued and stapled
- Reinforcing corner blocks are glued and stapled
- 8” anodized, brushed aluminum cylinder legs with adjustable glides.

Suspensions

- Seat and back suspension features heavy-duty Sytex stretch-webbing attached with ½” staples at 45 degree angle, minimum of 4 staples per inch secures webbing to frame.
- Sheet webbing suspension passes the following:
 - ✓ UFAC – Class 1
 - ✓ NFPA 260A – Class 1
 - ✓ CAL 117
 - ✓ FNE 83-258B
 - ✓ BIFMA

Foam

- CFC-free, Bio-Flex™ Hybrid includes soy-based foam
- Seat: Part 1 = 4.5” thick 1.8 Den. 35 UC; Part 2 = .5” thick 1.5 Density 45 CFR
- Back: Part 1 = 3” thick 1.4 Den. 27 CFR; Part 2 & 3 = .5” thick 1.5 Density 45 CFR
- CAL TB117-2013 rated

Upholsteries

- Standard fabrics Cal TB117-2013 rated and tested for high wear (most, more than 30,000 double rubs Wyzenbeek test).
- See individual upholstery specification sheet(s) for details regarding stain resistance, anti-microbial, moisture resistance, CAL-133 compliance, etc.
- Designed to accept leather, faux leather and vinyl upholsteries as well

Exterior

- Fully upholstered with double-needle trim on seat and back to reinforce sewing
- Extra high back offers comfort and privacy in open collaborative areas
- Brushed aluminum cylinder legs with adjustable glides
- Easily connects with linear or curved seating units or tables to provide contemporary solution of multiple configurations for reception areas, lobbies or waiting rooms

Dimensions

- Overall: 74.5”W x 36.5”D x 52.75”H
- Seat: 44-63.5”W x 20”D x 19.5”H
- Back Height from seat: 33.75”

Warranty

- Limited Lifetime
- Meets or exceeds ANSI/BIFMA 5.4-2005 Lounge Seating Tests

Ships

Truck fully assembled

Ship Weight: 191

Ship Cubes: 86.22

Freight Class: 250



Environmental & Sustainability

Materials & Resources

Standard material use in products in accordance with the following standards:

- LEED for Commercial Interiors EA Credit 2.1, 50% Construction Waste Diversion (1 point)
- LEED for Commercial Interiors EA Credit 2.2, 75% Construction Waste Diversion (1 point)
- ANSI/BIFMA e3-2011e (level®) Credit 5.10.2, 100% solid waste diversion
- LEED for Commercial Interiors EA Credit 3.3, Resource Reuse 30%, Furniture & Furnishings (1point) - HPFI Lifetime warranty and Second Life program applicable for reuse
- ANSI/BIFMA e3-2011e (level®) Credit 5.9.4, Extended Product Responsibility - HPFI Second Life program ensures reuse of usable product
- LEED for Commercial Interiors MR Credit 5.1, Regional Materials 20% (1 point) - HPFI products are manufactured in High Point, NC and may contribute this point based on project location.