

Specifications

HPFi

Flex Lounge

15012 Two-Sided, One-Seat Chair



Frame

- Engineered hardwood frame components are glued and stapled
- Corner Blocks are glued and screwed

Foam

- CFC-free, Bio-Flex™ Hybrid includes soy-based foam
- CAL TB117-2013 rated
- Top surface: 3" thick, 1.8 Density, 36 CFR
- Vertical surfaces: .5" thick, 1.5 Density, 45 CFR

Upholsteries

- Standard fabrics CAL TB117-2013 rated and tested for high wear (most more than 30,000 double rubs Wyzenbeek Wire Mesh test).
- Woven Cryptons treated with Perma Block or vinyls with Blockade/Nano-cide which are anti-bacterial, anti-microbial and mildew resistant
- See individual swatches for technical specifications
- Available in textile or coated fabric upholsteries in a single or two-tone

Exterior

- Fully Upholstered top and sides, non-woven Cambric (polypropylene) bottom
- Non-marring, black .75" H non-adjustable, cylindrical glides

Dimensions

- Overall: 20"W x 50"D x 30"H
- Seat height: 18"
- Seat depth: 20"
- Seat width: 20"
- Back height 10"

Warranty

- Limited Lifetime
- Meets or exceeds industry test standards for Lounge Seating

Ships

- Fully Assembled by Truck
- Ship Weight: 120 lb.
- Ship Cubes: 29
- Freight Class: 250

Environmental & Sustainability

Materials & Resources



Standard material use in products in accordance with the following standards:

- LEED for Commercial Interiors EA Credit, 50% Construction Waste Diversion (1 point)
- LEED for Commercial Interiors EA Credit, 75% Construction Waste Diversion (1 point)
- LEED for Commercial Interiors EA Credit, Resource Reuse 30%, Furniture & Furnishings (1 point) - HPFi Lifetime warranty and Second Life program applicable for reuse
- LEED for Commercial Interiors MR Credit, Regional Materials 20% (1 point) - HPFi products are manufactured in High Point, NC and may contribute this point based on project location.