Specifications

HPFi

Flex

2032-OF 2-Tier, 30° Outside Facing Seating

Frame

- Engineered hardwood frame components
- Corner blocks glued and stapled

Foam

- CFC-free, Bio-Flex™ Hybrid includes soy-based foam
- CAL TB117-2013 rated
- Seats: 2' thick, 2.5 Density, #55 Ultra-cell
- Vertical Surfaces: .5" thick, 1.5 Density, 45 CFR

Upholsteries

- CAL TB117-2013 rated
- Standard fabrics tested for high wear (most more than 30,000 double rubs Wyzenbeek Wire Mesh test)
- See individual upholsteries specification sheet(s) for details regarding stain resistance, anti-microbial, moisture resistance, etc.
- Available in textile or coated fabric upholsteries in a single or two-tone
- Seam Slippage/Strength rating must be a minimum 40 lb. rating on warp and weft (fill) on horizontal surfaces/steps

Exterior

- Fully upholstered top, back and sides
- Non-woven Cambric (polyproylene) bottom
- Adjustable glides

Dimensions

- Overall: 45.5"W x 39.5"D x 35"H
- Seat heights:
  Tier 1: 18"
  Tier 2: 35"
- Seat depth:
  Tier 1: 18.75"
  Tier 2: 20"
- Seat width:
  Tier 1: 36" - 45.5"
  Tier 2: 25.5" - 36"

Warranty

- Limited Lifetime
- Meets or exceeds industry test standards for Lounge Seating

Ships

- Fully Assembled by Truck
- Ship Weight: 126 lb.
- Ship Cubes: 44
- Freight Class: 200

Environmental & Sustainability
Materials & Resources

Standard material use in products in accordance with the following standards:

- LEED for Commercial Interiors EA Credit, 50% Construction Waste Diversion (1 point)
- LEED for Commercial Interiors EA Credit, 75% Construction Waste Diversion (1 point)
- LEED for Commercial Interiors EA Credit, Resource Reuse 30%, Furniture & Furnishings (1point) - HPFi Lifetime warranty and Second Life program applicable for reuse
- LEED for Commercial Interiors MR Credit, Regional Materials 20% (1 point) - HPFi products are manufactured in High Point, NC and may contribute this point based on project location.