Specifications

HPFi

Flex

2373-IF 3-Tier, 30° Inside Facing Seating, Wood "Steps"



Frame

- Engineered hardwood components
- Corner blocks glued and stapled

Foam

- CFC-free, Bio-Flex™ Hybrid includes soy-based foam
- CAL TB117-2013 rated
- .5" thick, 1.5 Density, 45 CFR (vertical surfaces)

Upholsteries

- CAL TB117-2013 rated
- Standard fabrics tested for high wear (most more than 30,000 double rubs Wyzenbeek Wire Mesh test)
- See individual upholsteries specification sheet(s) for details regarding stain resistance, anti-microbial, moisture resistance, etc.
- Vertical surfaces available in textile or coated fabrics in a single or two-tone

Exterior

- Maple veneer on Birch engineered hardwood horizontal surfaces (steps)
- Upholstered back, sides and front of "steps"
- Non-woven Cambric (polyproylene) bottom
- Adjustable glides

Dimensions

- Overall: 46"W x 39.5"D x 35"H
- Seat heights:
  Tier 1: 10.5"
  Tier 2: 27"
  Tier 3: 35"
- Seat depth:
  Tier 1: 11.5"
  Tier 2: 17.5"
  Tier 3: 10.5
- Seat width:
  Tier 1: 26" - 32"
  Tier 2: 32" - 41"
  Tier 3: 41.5" - 46"

Warranty

- Limited Lifetime
- Meets or exceeds industry test standards for Lounge Seating

Ships

- Fully Assembled by Truck
- Ship Weight: 126 lb.
- Ship Cubes: 45
- Freight Class: 250

Environmental & Sustainability
Materials & Resources

Standard material use in products in accordance with the following standards:

- LEED for Commercial Interiors EA Credit, 50% Construction Waste Diversion (1 point)
- LEED for Commercial Interiors EA Credit, 75% Construction Waste Diversion (1 point)
- LEED for Commercial Interiors EA Credit, Resource Reuse 30%, Furniture & Furnishings (1point) - HPFi Lifetime warranty and Second Life program applicable for reuse
- LEED for Commercial Interiors MR Credit, Regional Materials 20% (1 point) - HPFi products are manufactured in High Point, NC and may contribute this point based on project location.